



Rated Load (kg)	Nº of people	Speed (m/s)	Entrances Nº/Angle	Car Size		Shaft Size		Pit	Headroom	Doors**	Machine*** Power/Current
				Width	Depth	Width	Depth*				
300	4	1	1/0°	800	1050	1300	1275	1050	3400	2PSO 700	WYJ140-10-450-2 3Kw / IN= 8A IS= 11,2 A
			2/180°		1100	1300	1430				
			1/0°	900	950	1400	1175				
			2/180°		1000	1400	1330				
375	5		1/0°	850	1200	1350	1425				
			2/180°			1350	1530				
			1/0°	900	1100	1400	1325				
			2/180°			1400	1430				
450	6	1/0°	1000	1200	1500	1425					
		2/180°			1500	1530					
		1/0°		1250	1500	1475					
		2/180°			1500	1580					
630	8	1/0°	1100	1400	1600	1675					
		2/180°			1600	1775					
		1/0°			1800	1625					
		2/180°			1800	1725					
		1/0°			1950	1625					
		2/180°			1950	1725					
										2PSO 900	WYJ140-10-630-2 4,3Kw / IN= 11,5 A IS=16,1 A
										2PCO 800	
										2PCO 900	
										2PCO 900	

*Shaft depth dimensions consider landing doors 25mm inside the shaft.

**Calculations made for SELCOM WITTUR AUGUSTA EVO doors.

***Alternative machines are available for this lift model.

Unless stated otherwise, all dimensions are expressed in millimetres.

Operational ranges

Shaft	Pit:	Standard minimum: 1050 mm Reduced EN81-21 minimum: 800mm
	Headroom:	Standard minimum (2200 mm high car): 3400 mm Reduced minimum (2050 mm high car): 3250 mm
	Minimum width:	Car width + 500 mm
Car	Minimum width:	800 mm
	Maximum width:	1300 mm
	Minimum depth:	950 mm, single entrance 1050, double entrance
	Maximum depth:	1500 mm
	Standard Height:	2200 mm



Click here for more information about this product
www.gle-lifts.com