

Quotation Data Sheet



Customer (your company name):

Ouotation deadline

Your Reference/Job No.:

Date:

LIFT MODEL:

RHINO LIFT (goods-only)

RHINO LIFT PRO (goods with attendant)

UNITS:

Nº OF STOPS:

TRAVEL (max. 9m):

LOAD:

500kg

1000kg

1500kg

2000kg

CAR ENTRANCES:

Single

Through

No of floors Oo entrance:

No of floors 1800 entrance.

CAR DIMENSIONS (see tables in catalogue):

Width (mm):

Depth (mm):

PIT (mm):

(A ramp can be supplied in cases where no pit is available. Please select in options section below)

HEADROOM (mm):

CONTROL PANEL LOCATION:

Top floor adjacent to shaft

Lowest floor adjacent to shaft

Other floor:

POWER SUPPLY:

380V 3-phase

400V 3-phase

415V 3-phase

FREQUENCY:

50Hz.

60Hz.

LANDING DOORS:

Manual Swing (Epoxy RAL9005)

Manual Swing (St. steel)

Manual Shutter gate (Galvanised)

CAR DOOR (Picket gate):

Yes

No

CAR WALLS:

Epoxy (RAL7032 Beige)

Other

BUMP RAILS:

Wood

St. steel

PVC

No of levels:

FLOORING:

Steel plate (RAL7032 Beige)

FLO1 Black rubber circles

FLO5 Aluminium chequer plate

CEILING:

Open ceiling with galvanised steel beams and fluorescent lighting.

Closed ceiling with galvanised metal sheets and fluorescent lighting.

Closed ceiling with galvanised metal sheets and LED tube lighting.

INSTALLATION KITS (recommended in case installer doesn't have one):

Kit A: If space above steel tower is > 500mm

Kit B: If space above steel tower is < 500mm and car depth is <= 1.550 mm

Kit C: If space above steel tower is < 500mm and car depth is >= 1.550 mm

Structure installation platforms (6 units)



Quotation Data Sheet



PUSH BUTTONS:

BF (DMG)

US91 (Dewhurst)

M10 (Dewhurst)

RHINO LIFT AND RHINO LIFT PRO OPTIONS:

UCM Unintended car movement (included as standard in RHINO LIFT PRO).

Out-of-service key switch.

Ladder with supports to access the rescue hatch and locks.

BMS - Alarm

BMS - Lift position

Car door electrical interlock

Primed steel 100mm ramp (if no pit is available)

Aluminium chequer plate 100mm ramp (if no pit is available)

Car light timer

2.5m guides (standard is 5m)

Landing indicator

Landing keypad access control

RHINO LIFT PRO OPTIONS:

Attendant control key switch

3hr emergency car light

Firemen operation

Autodialler

Inductive loop

GSM

Telephone module located underneath car

Intercom between car operating panel and control panel

Car indicator

Voice synthesiser

COP engravings

LOP indicator

Alarm push button inside pit

Alarm push button on car top

OBSERVATIONS:



